## Amendment to the Claims:

This listing of claims will replace all prior versions, and listing, of claims in the application.

## **Listing of Claims**:

(currently amended): An intrinsically safe operating system, comprising:
a communication device having communication device type certification parameters
stored therein;

a peripheral device that attaches to the communication device, the peripheral device having peripheral device type certification parameters stored therein; and

the communication device restricting the operation of the peripheral device when the communication device type certification parameters and peripheral device type certification parameters are incompatible, based solely on a reading initiated by the communication device.

2. (currently amended): A method of providing an intrinsically safe communication system, comprising the steps of:

storing communication device type certification parameters within a communication device;

storing peripheral type certification parameters within a peripheral device; coupling the peripheral device to the communication device; and

initiating a read at the radio to determine determine whether the peripheral device is intrinsically compatible with the communication device based on the communication device type certification parameters and the peripheral type certification parameters.

- 3. (original): The method of claim 2, wherein the communication device is a handhold communication device.
- 4. (original): The method of claim 2, wherein the peripheral device comprises an accessory.
- 5. (original): The method of claim 2, wherein the peripheral device comprises a battery.

6. (currently amended): A method of ensuring intrinsically safe operation of a radio and a peripheral device, comprising:

storing radio type certification parameters within the radio;

storing peripheral device type certification parameters within the peripheral device;

comparing, at the radio, the radio type certification parameters and peripheral type certification parameters;

determining, solely at the radio, intrinsically safe compatibility based on the step of comparing; and

indicating intrinsically safe incompatibility.

- 7. (original): The method of claim 6, further comprising restricting the operation of the radio in response to the step of comparing.
- 8. (original): The method of claim 6, further comprising restricting the operation of the peripheral in response to the step of comparing.
- 9. (original): The method of claim 6, wherein indicating comprises sending a visual alert to a user.
- 10. (original): The method of claim 6, wherein indicating comprises sending an audible alert to the user.

Docket No. CM06341J

Application No. 10/649,445 Amendment dated September 13, 2005 Reply to Office Action of May 27, 2005

11. (original): The method of claim 6, wherein indicating comprises sending a physical alert to the user.

12. (original): An intrinsically safe operating system, comprising:

a communication device having communication device type certification parameters stored therein;

a plurality of peripheral devices that attach to the communication device, the plurality of peripheral devices each having peripheral device type certification parameters stored therein; and

the communication device restricting the plurality of peripheral devices to various predetermined levels of operation in response to the communication device type certification parameters and the peripheral device type certification parameters being mismatched.

13. (original): The intrinsically safe operating system of claim 12, wherein the plurality of peripheral devices includes a battery and accessories coupled to the communication device.

No.9325 P. 10

Application No. 10/849,445 Amendment dated September 13, 2005 Reply to Office Action of May 27, 2005

14. (original): A method of providing an intrinsically safe communication system, comprising the steps of:

storing communication device type certification parameters within a communication device;

storing peripheral type certification parameters within a plurality of peripheral devices; coupling the plurality of peripheral devices to the communication device; determining whether the plurality of peripheral devices are intrinsically compatible with the communication device based on the communication device type certification parameters and each of the peripheral type certification parameters; and

selectively restricting operation of the plurality of peripheral devices based on intrinsic compatibility.

- 15. (original): The method of claim 14, wherein the plurality of peripheral devices includes a battery and accessories coupled to the communication device.
- 16. (new claim): The intrinsically safe operating system as described in claim 1, wherein the peripheral device is processor-less as regards to the intrinsically safe operating system.
- 17. (new claim): The method of claim 2, wherein the peripheral device is processor-less as regards to the intrinsically safe communication system.

- 18. (new claim): The method of claim 6, wherein the peripheral device is processorless as regards to the intrinsically safe operation of the radio and the peripheral device.
  - 19. (new claim): The intrinsically safe operating system as described in claim 12, wherein the plurality of peripheral devices are processor-less as regards to the intrinsically safe operating system.
  - 20. (new claim): The method of claim 14, wherein the plurality of peripheral devices are processor-less as regards to the intrinsically safe communication system.
  - 21. (new claim): The intrinsically safe operating system of claim 12, wherein the communication device bases the restricting solely on determinations made within the communication device.
  - 22. (new claim): The intrinsically safe operating system of claim 14, wherein the steps of determining and selectively restricting are made solely within the communication device.